

**IMPORTANT! Please read all instructions before installing.**

Thank you for purchasing a Shakespeare antenna product. Shakespeare works hard to build reliability and durability into all of its products for maximum customer satisfaction.

The 396-1-AIS is a center-fed, 1/2-wave, coaxial sleeve VHF marine antenna of 4' (1.2 m) overall length. It is specifically designed for use with AIS equipment, and meets the strict requirements of the AIS specification. This one-section antenna has an aluminum sleeve for mast mounting.

**TOOLS REQUIRED:**

- 7/16" wrench

**INSTALLATION INSTRUCTIONS**

Choose a mounting location that is as high as possible, as free as possible from obstructions, and as far as possible away from other antennas and strong sources of RF.

1. Mount the antenna to your mast using the supplied 1 1/4" U-bolts, clamps, lockwashers, washers, and hex nuts, as illustrated in the diagram. The Style 396-1-AIS can be strapped to a larger mast if steel banding (not supplied) is used.
2. Connect the antenna to your AIS-enabled equipment with 50-ohm low-loss coax cable with PL-259 connectors on each end (each sold separately). Route the cable as far as possible from other electrical equipment and cables.

This antenna requires no external or internal ground system, and works equally well on fiberglass, wood, or metal boats.


**CLEANING INSTRUCTIONS**

To clean the antenna, use mild dish washing liquid (one that is not harsh to the hands and without ammonia) in lukewarm water.

**SUPPLIED PARTS:**

- 1 Antenna Assembly
- 2 U-bolts
- 2 Clamps
- 4 Washers
- 4 Lockwashers
- 4 Hex Nuts

**TECH TIP:** This antenna will read "open" when tested with an ohm meter or continuity tester.



**SHAKESPEARE® MARINE**  
www.shakespeare-marine.com

U.S. Operations: 6111 Shakespeare Rd. · Columbia, SC 29223 · 803-227-1590 · 800-845-7750

U.K. Operations: Enterprise Way, Fleetwood, Lancashire, FY7 8RY, England · +44 (0) 1253 858787 · Fax: +44 (0) 1253-859595